

# TECHNICAL DATA REPORT

HS 0785

## GRIP Mild Concrete Etch

### DESCRIPTION:

Mix of mineral and organic acids, wetting agents and inhibitors.

### PURPOSE:

To clean and remove surface dust from freshly poured concrete to enable a sealant such as AQUASEAL 100 anchor itself in the concrete and prevents the concrete from dusting.

### HOW TO USE:

Mix 1 part with 6 - 10 parts water depending on amount of soils. Spray with low pressure sprayer directly on to surfaces or brush on with an acid resistant brush. Let soak for a few minutes, agitate lightly and rinse off with water.

### MAIN USERS:

Garages, warehouses, factory floors, fire halls, arenas, apartment buildings, etc.

### ADVANTAGES:

- 1) Works quickly.
- 2) Removes a wide variety of soils, greases, soap scum and calcium stains from ceramic tile and painted pool surfaces.
- 3) Pleasant odour, non-fuming.
- 4) Easy to apply.
- 5) Easy to rinse.
- 6) Biodegradable.

### PRECAUTIONS:

EXTERNAL: If splashed in eyes or on skin flush thoroughly with water for 15 minutes, then cover with moistened sodium bicarbonate. **GET MEDICAL ATTENTION IMMEDIATELY.** If splashed on clothing remove and wash them immediately.

INTERNAL: If swallowed, give solution of milk and sodium bicarbonate, milk of magnesia or egg whites beaten with water or three to four glasses of milk. **DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.**

Read Material Safety Data Sheet.

### SPECIFICATIONS:

pH	1.0 - 1.2
Density at 20°C	1.03 - 1.07
Physical Form	Clear liquid
Colour	Dark green
Odour	Pleasant
Stability	Stable between -17°C and 55°C
Compatibility	Do not mix with other chemicals