

# TECHNICAL DATA REPORT

HS 1194

## MAXILUBE XL Conveyor Lubricant

### DESCRIPTION:

MAXILUBE XL is a viscous amber liquid manufacture from a base of selected fatty acids and hardness control agents.

### PURPOSE:

MAXILUBE XL is used to lubricate conveyor chains in bottle filling plants and provide lubrication between bottles and metal conveyor.

### HOW TO USE:

MAXILUBE XL is diluted with from 1 to 120 up to 1 to 150 with water, depending on the degree of hardness of the water and the speed of the conveyor chain. Foam is controlled with an effective anti-foaming agent.  
**ALWAYS RINSE WITH POTABLE WATER THE SURFACES THAT MAY COME INTO CONTACT WITH FOOD.**

### PRINCIPAL USERS:

Breweries, dairies, water and soft drink bottling plants and food processing industries that fill glass or plastic containers.

### ADVANTAGES:

- 1) Very concentrated.
- 2) Anti-oxidant for the conveyor chain.
- 3) Clean the conveyor chain.
- 4) Prevents odour from forming.
- 5) Formulated for high speed production.
- 6) Prevents "kinking" of the conveyor chains.
- 7) Prevents bottles or containers from falling over.
- 8) Approved for Food Plant Use, file P216 n1.
- 9) Made from biodegradable and renewable materials.

### PRECAUTIONS:

Do not get in eyes. Keep out of reach of children.  
Read Material Safety Data Sheet.

### SPECIFICATIONS:

Appearance .....	Clear amber liquid
pH .....	9.5 - 10.5
Viscosity .....	60 - 70 cps
Density .....	1.025
Biodegradable .....	Yes