

TECHNICAL DATA REPORT

HS 4040

DRY SILICONE **Silicone Release Agent and Multi-Purpose Dry Lubricant**

DESCRIPTION:

DRY SILICONE is a clear colourless liquid, containing Polysiloxane resins.

PURPOSE:

DRY SILICONE is a heat stable, non-toxic and odourless polymer which lubricates, protects, reduces friction and forms a stick free surface wherever it is needed.

HOW TO USE:

Clean surface thoroughly with a suitable cleaner and allow to dry. Remove all grease, curing compounds, surface treatments, coatings, oils, etc. Using a suitable sprayer, apply DRY SILICONE uniformly and lightly to the surface. Allow to dry. For highly porous surfaces, a second application may be required. DRY SILICONE will cover an area of approximately 2.5 to 10 m² per litre, depending on the porosity of the surface.

MAIN USERS:

Electrical contractors, repair shops, needle trade, printers, electronic repair shops, pinball arcades, bowling alleys, equipment rental companies, trucking lines, construction contractors, etc.

ADVANTAGES:

- 1) Can be used in temperature from -40°C to +200°C.
- 2) Not affected by water, oil or solvent.
- 3) Can be used on any surface; metals, rubber, plastics, fabric, painted surfaces.
- 4) Retards corrosion, rust and waterproofs.
- 5) Leaves surfaces non-sticking and water repellent.
- 6) Available in aerosol and bulk liquid.

PRECAUTIONS:

Avoid contact with eyes, contains aliphatic solvents. In case of contact with eyes, flush for 15 minutes with water and get medical attention. Read Material Safety Data Sheet.

SPECIFICATIONS:

Appearance	Clear liquid
Odour	Solvent
Flash Point	Minimal 93°C
Corrosion (ASTM 484)	Negative, pass