

TECHNICAL DATA REPORT

TI 8751

Clean Cut Cutting and Tapping Fluid

DESCRIPTION:

A transparent coolant and lubricant especially designed for portable and field operations: Machining, Punching, Sawing, Milling, Grinding, Cutting, Tapping and Threading.

PURPOSE:

Use of this product results in cooler work pieces, less heat distortion and tool burning, thereby increasing production and lengthening tool life. The fluid is transparent to allow for increase visibility of the work area.

HOW TO USE:

Spray area to be worked generously. Reapply as necessary to keep work area cool and well lubricated. Can be removed with cold water or Solvent SX

MAIN USERS:

Machine shops, mines, transport companies, garages, ready-mix companies, excavation contractors, paper mills, lumber and saw mills, refineries, etc.

ADVANTAGES:

- 1) Leaves no residue.
- 2) Can be used on exotic metals, such as, Hastelloy, Berylium-Copper, Titanium
- 3) Transparent fluid to increase visibility of the work area
- 4) Prolongs tool life.
- 5) Cooler work piece with less tool burning
- 6) Increases production rates.
- 7) Also available in bulk packaging.

PRECAUTIONS:

Contents under pressure, do not puncture or incinerate container. Use in a well ventilated area. Keep out of reach of children. Read the material safety data sheet.

SPECIFICATIONS:

Colour Clear transparent
Odour Slight alcohol odour
Freon content None